

# Print Service

The **COBI.wms Print Service** is an MS Windows service which receives commands from the Android app and triggers a print event on the Windows machine.

## How it works / Limitations

**Currently, the service only works in combination with Coresuite Remote Print.**

The service generates XML files and puts them in a folder that is scanned by Coresuite Designer, which takes care of the actual printing. This means, you must have Coresuite Designer installed and configured correctly to pick up XML files from a specific folder.

See here for the relevant Coresuite documentation:

[http://helpfiles.coresystems.ch/help/country\\_package/manual/en/index.html?des\\_configuration\\_batch\\_print.htm](http://helpfiles.coresystems.ch/help/country_package/manual/en/index.html?des_configuration_batch_print.htm)

Only the **User** and **Parameter Scan-Path** fields need to be filled out.

Also, if you don't have Coresuite Service, then at least one SAP Business One client must be running at all times for Coresuite Designer to process the XML files. See here for information about Coresuite Service:

<https://helpdesk.coresystems.ch/hc/en-us/articles/360034896353-Coresuite-Service>

(If either of the above links to the Coresuite documentation don't work, please notify [support@cobisoft.de](mailto:support@cobisoft.de) so we can update this page.)

XML files that are placed into the folder will be moved automatically into a sub-folder called `_executed` if the print job was successful, or into a sub-folder called `_error` if there was a problem. (These folders are created and managed automatically by Coresuite.) In case of an error, you can open the XML file in the `_error` folder (with Notepad or another text editor) and see if an error message was written into it. Usually, Coresuite writes the error message into these files in the form of an XML comment, near the end of the file.

**NOTE:** All of the above is done by Coresuite, not by the COBI.wms Print Service. If the XML files are not being processed, check if Coresuite is set up and running correctly. The job of the COBI.wms Print Service is done in the moment where the XML file is generated and put into the configured folder.

## Installation

Download: [cobiwms-print-service.zip](#)

1. Extract the contents of `cobiwms-print-service.zip` to `C:\cobiwms-print-service\`.
2. Run the following command in `cmd.exe` or PowerShell:  
`C:\Windows\Microsoft.NET\Framework64\v4.0.30319\InstallUtil.exe`

C:\cobiwms-print-service\cobiwms-print-service.exe

3. Create C:\cobiwms-print-service\config.json with contents like below.
4. You can now start/stop the service from the MS Windows Services application.

Example config for single-tenant setup (e.g. on-premises or private cloud):

```
{
  "ListenPort": 9110,
  "TenantConfig": [
    {
      "PrintDirectory": "C:\\CoresuiteRemotePrint\\Productive"
    }
  ]
}
```

The **PrintDirectory** must correspond to the **Parameter Scan-Path** of the Coresuite Designer configuration; see above.

Example config for multi-tenant setup (e.g. public cloud):

```
{
  "ListenPort": 9110,
  "TenantConfig": [
    {
      "AuthToken": "SECRET_1",
      "PrintDirectory": "C:\\CoresuiteRemotePrint\\Tenant_1\\Productive"
    },
    {
      "AuthToken": "SECRET_2",
      "PrintDirectory": "C:\\CoresuiteRemotePrint\\Tenant_2\\Productive"
    }
  ]
}
```

In a multi-tenant environment, the correct AuthToken must be entered in the COBI.wms [Print Settings](#) screen for the app to be able to trigger print jobs. The token serves both to identify the tenant, and as a password to ensure that tenants running on the same cloud environment cannot accidentally or intentionally trigger print jobs for each other.

Note that the COBI.wms Print Service does not support encrypted communication. This means that if you make the TCP port of the Print Service open to the Internet, and set up COBI.wms to contact it, then the tokens will be sent unencrypted over the Internet. It is strongly advised to set up a VPN connection in this scenario to ensure encrypted communication.

## Update

1. Stop the service.
2. Extract the contents of the new ZIP file into C:\cobiwms-print-service\.
3. Start the service.

# Uninstall

1. Stop the service.
2. Run the following command in cmd.exe or PowerShell:  
C:\Windows\Microsoft.NET\Framework64\v4.0.30319\InstallUtil.exe /u  
C:\cobiwms-print-service\cobiwms-print-service.exe
3. Delete the folder C:\cobiwms-print-service\.

From:

<https://docs.cobisoft.de/wiki/> - **COBISOFT Documentation**

Permanent link:

[https://docs.cobisoft.de/wiki/cobi.wms/print\\_service?rev=1684934115](https://docs.cobisoft.de/wiki/cobi.wms/print_service?rev=1684934115)

Last update: **2023/05/24 15:15**

