

# Print Settings

COBI.wms supports two types of printing:

- Contacting a network printer directly from the mobile device
- Contacting the COBI.wms Print Helper running on a Windows Server

The first option is mostly suitable for printing wares labels, and the second for printing booked documents. Correspondingly, the Print Settings screen of the Android app is split into these two sections:

## Label printing

This type of printing requires a network-capable printer, but no additional server-side software. The Android device will contact the IP Address of the printer in the local network and send it the document to print.

### Method

Under the label printing setting, you will notice that there is once again a choice of two methods: **Android standard** and **ZPL-compatible**.

Choosing the Android standard method means that whenever you want the app to print a label, it will generate the page to be printed but delegate the actual printing task to the Android operating system. This requires your network printer to be compatible with Android, which is often not the case.

The ZPL-compatible method will make the app construct print commands in the [Zebra Programming Language](#) and send them directly to the printer, bypassing the Android system. While ZPL was developed by Zebra initially, it has become a de facto standard in the industry, meaning that most label printer brands (such as TSC, cab, Brady, Godex, etc.) support ZPL emulation, making them all compatible with COBI.wms.

### ZPL printer addresses

As the name implies, this setting is only needed if you choose the **ZPL-compatible** method for label printing.

The text field must be filled with the IP addresses of the ZPL-compatible network printers, one IP address per line. If your printers have resolvable names in your local DNS, you may of course also use their host names instead of IP addresses.

### ZPL TCP send buffer size

Most of the time, this field can be left empty. However, a small number of ZPL-compatible network

printers might have a peculiar TCP/IP implementation which requires the TCP send buffer to be set to a particular size. For example, printers from the brand **Godex** might require this field to have the value of **1024**.

## Document printing

This type of printing requires the COBI.wms Print Helper to be installed on a Windows Server that can be reached from the Android mobile devices.

Currently, the document printing feature works solely in combination with **coresuite designer** layouts.

### Print service address

This text field must be filled with the IP address or host name of the Windows Server on which the COBI.wms Print Helper service is running.

The default port is 9110. If you configured the helper service to use a different TCP port, then you must specify the port number via the format <host>:<port> in this field.

For example, if the Windows Server has the IP address 192.168.16.20 and the port number of the COBI.wms Print Helper is configured to be 9120, then the text field must contain:  
192.168.16.20:9120

### Print Mode, Layout ID, and Print Def settings

The rest of the print settings screen consists of **Print Mode**, **Layout ID**, and **Print Def** fields for each type of booking where the app supports printing. These values must correspond to the the coresuite print modes, designer layout IDs, and print definitions.

From:

<https://docs.cobisoft.de/wiki/> - COBISOFT Documentation

Permanent link:

[https://docs.cobisoft.de/wiki/cobi.wms/print\\_settings?rev=1635518816](https://docs.cobisoft.de/wiki/cobi.wms/print_settings?rev=1635518816)

Last update: **2021/10/29 16:46**

